

BLUECONTROL MINI DAIRY

THE NEW, COMPACT VARIANT OF BLUECONTROL




- Remote connectivity from anywhere with FarmOnline™ application
- Available in 36 languages
- User-friendly with default dashboard and a customizable house overview



For more information

skov-secco.com info@skov-secco.com



BLUECONTROL MINI DAIRY

THE NEW, COMPACT VARIANT OF BLUECONTROL

Features:

- Also known as DOL 432, this controller is tailored for smaller systems with simplified equipment control requirements.
- Designed for the North American market and cULus certified.
- Effortlessly compatible with Natural, LPV, and Tunnel ventilation types (available within BlueControl Mini Dairy software).
- Comes with 12 relays. The 0-10 V inputs and outputs of the main module can be configured in the following way:
 - 11 inputs and 2 outputs - or
 - 9 inputs and 4 outputs - or
 - 7 inputs and 6 outputs.
- Password-protected function to prevent unauthorized changes, with three different user access levels.
- Temperature and humidity monitoring and adjustment, and pressure level monitoring.
- Enables cooling control by monitoring temperature and humidity levels.
- Wind speed and direction monitoring, and rain detection and adjustment for regulating curtains in the Natural ventilation mode.
- Temperature Humidity Index (THI) monitoring and adjustment along with heat stress alerts.
- Alarm output to external alarm system.
- Data are updated in real-time in both the climate controller and FarmOnline™ application.
- Software is available in 36 languages, including English, French, German, Japanese, Chinese, Spanish, Arabic, and more!



For more information

skov-secco.com

info@skov-secco.com

