

MEGAFAN Püre

TUNNEL VENTILATION

Püre
BY SECCO



VERY HIGH PERFORMANCE AND UNIQUE DIRECT DRIVE DESIGN

- Thick and corrosion-resistant fiberglass housings with a lifetime warranty (The Püre model is grey).
- Totally enclosed, maintenance-free, high efficiency, and U-CSA-C or CE-approved motors.
- Shipped fully assembled, except for discharge cones and guards.
- Extremely quiet operation on all speeds.
- **NO PULLEYS, NO BELTS, NO MAINTENANCE.**
- The gear motor technology is a modular system complete

with an energy-efficient motor and an adapted gear unit optimally matched to each other. Without couplings and transmission elements, this high-quality system represents the optimum drive solution.

- Three years warranty on the motor and on the blades.
- Full one-year warranty on all other parts.

THE LARGEST MOST EFFICIENT FAN ON THE MARKET ▶

SIZE	DRIVE	BLADE MODEL	SHUTTER OR GUARD	HP (KW)	VOLT	PH	AMP	RPM	HZ	WATTS USED	CFM (M ³ /H) 0" SP	CFM/WATT (M ³ /H/WATT) 0" SP	CFM (M ³ /H) .05" SP	CFM/WATT (M ³ /H/WATT) .05" SP	CFM (M ³ /H) .10" SP	CFM/WATT (M ³ /H/WATT) .10" SP	CFM (M ³ /H) .125" SP	CFM/WATT (M ³ /H/WATT) .125" SP	CFM (M ³ /H) .20" SP	CFM/WATT (M ³ /H/WATT) .20" SP	AFR %	SPEED	ROUGH OPENING
78"(198 CM)	DD	6 BLADES POLYAMIDE	GUARD	3 (2.25 kW)	230/460	3	8.4/4.2	298	50/60	1778	52 490 (89 233)	26.0 (44.1)	48 600 (82 620)	23.8 (40.5)	47 110 (80 087)	21.6 (36.7)	46 137 (78 433)	20.2 (34.3)	40 840 (69 428)	16.7 (28.4)	78%	VARIABLE	82.5" L X 83" H (209 L X 211 H CM)
78"(198 CM)	DD	6 BLADES POLYAMIDE	SHUTTER	3 (2.25 kW)	230/460	3	8.4/4.2	293	50/60	1711	52 490 (89 233)	26.4 (44.8)	48 600 (82 620)	23.3 (39.6)	47 110 (80 087)	20.7 (35.2)	45 114 (76 694)	19.4 (33.0)	40 840 (69 428)	14.4 (24.5)	78%	VARIABLE	82.5" L X 83" H (209 L X 211 H CM)
78"(198 CM)	DD	6 BLADES ALUMINUM	GUARD	3 (2.25 kW)	230/460	3	8.4/4.2	293	50/60	1627	52 290 (88 893)	28.3 (48.1)	51 150 (86 955)	25.1 (42.7)	49 120 (83 504)	22.5 (38.3)	46 006 (78 210)	21.1 (35.9)	43 820 (74 494)	17.3 (29.4)	84%	VARIABLE	82.5" L X 83" H (209 L X 211 H CM)
78"(198 CM)	DD	6 BLADES ALUMINUM	SHUTTER	3 (2.25 kW)	230/460	3	8.4/4.2	293	50/60	1711	52 290 (88 893)	25.9 (44.1)	51 150 (86 955)	23.3 (39.6)	49 120 (83 504)	21.0 (35.7)	44 372 (75 432)	19.1 (32.5)	43 820 (74 494)	14.0 (23.8)	84%	VARIABLE	82.5" L X 83" H (209 L X 211 H CM)

*The data above is based on testing performed by an independent accredited lab using ANSI/AMCA 210-07 standards.

FEATURES

- Highly efficient 6-bladed fan with fiberglass-reinforced polyamide blades.
- Optional balanced heavy-duty corrosion resistant 6 aluminum blades propeller.
- On high speed produces 52 490 CFM (89 233 m³/h) and 26.4 CFM/watt (44.8 m³/h) at 0" static pressure.
- A variable frequency drive allows you a smooth speed adjustment from 350 RPM down to 80 RPM. Fan power consumption reduces with speed.
Make sure you have a minimum shutter opening at a low speed of 1" (2.54 cm).
- Contains a German synthetic oil specially designed for a long lifespan.
- Consumption is 2.25 kW on high speed.
- Motors are UL/CSA/CE approved, 50/60 Hz, and are IE3 certified.



For more information

skov-secco.com

info@skov-secco.com



Hedelund 4, Glyngoere, 7870 Roslev, Denmark
Phone.: +45 72 17 55 55

4040, boul. Casavant West
St-Hyacinthe (Quebec) Canada • J2S 8E3
Phone.: +1 877 711.0777

160 Claremont, Avenue, Suite 200,
GA 30030, Decatur, USA
Phone: +1 (678) 954 5743

