

CHIMNEYS & ROOF VENTS


NATURAL VENTILATION

SQUARE CHIMNEY



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm).
- Bird barrier available.
- Custom built according to roof slope to prevent any water flow.
- Insulated and light, rigid model.

DAMPER



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" or 19" x 30" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm or 483 x 762 mm).
- Insulated and light, rigid model.
- Can be installed in the top or bottom.
- Automatic or manual adjustment control.

RECTANGULAR CHIMNEY



- Inside dimensions of 19" x 30" (483 x 762 mm).
- Bird barrier available.
- Custom built according to roof slope to prevent any water flow.
- Insulated and light, rigid model.
- Available with a flange welded on the opposite side.

LINEAR ROOF VENT



- Inside dimensions of 8" x 48" (203 x 1220 mm) or 8" x 96" (203 x 2448 mm).
- Standard roof slope included.
- Allows ventilating the attic.
- Ventilates 1000 sq. feet (100 m²) or 2000 sq. feet (200 m²).
- Insulated and light, rigid model.

CHIMNEY DUCTING



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" or 19" x 30" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm or 483 x 762 mm).
- Delivered unassembled for freight savings.
- Insulated and light, rigid model.



**ALL PLASTIC PRODUCTS
MANUFACTURED BY SKOV-SECCO
ARE MADE OF STURDY AND NON-
CORROSIVE UV-TREATED H.D.P.E.
PLASTIC.**



For more information
skov-secco.com

info@skov-secco.com

