

CHIMNEYS & ROOF VENTS


NATURAL VENTILATION

SQUARE CHIMNEY



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm)
- Bird barrier available
- Custom built according to roof slope to prevent any water flow
- Insulated and light, rigid model

DAMPER



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" or 19" x 30" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm or 483 x 762 mm)
- Insulated and light, rigid model
- Can be installed in the top or bottom
- Automatic or manual adjustment control

RECTANGULAR CHIMNEY



- Inside dimensions of 19" x 30" (483 x 762 mm)
- Bird barrier available
- Custom built according to roof slope to prevent any water flow
- Insulated and light, rigid model
- Available with a flange welded on the opposite side

LINEAR ROOF VENT



- Inside dimensions of 8" x 48" (203 x 1220 mm) or 8" x 96" (203 x 2448 mm)
- Standard roof slope included
- Allows ventilating the attic
- Ventilates 1000 sq. feet (100 m²) or 2000 sq. feet (200 m²)
- Insulated and light, rigid model

CHIMNEY DUCTING



- Inside dimensions of 19" x 19" or 24" x 24" or 30" x 30" or 36" x 36" or 40" x 40" or 19" x 30" (483 x 483 mm or 610 x 610 mm or 762 x 762 mm or 915 x 915 mm or 1016 x 1016 mm or 483 x 762 mm)
- Delivered unassembled for freight savings
- Insulated and light, rigid model

**ALL PLASTIC PRODUCTS
MANUFACTURED BY SECCO ARE
MADE OF STURDY AND NON-
CORROSIVE UV-TREATED H.D.P.E.
PLASTIC. THESE PRODUCTS ARE
COVERED BY A FULL WARRANTY
OF 5 YEARS.**



For more information

seccointernational.com

Distributed by:

Secco International Inc.
4040, Blvd Casavant West
St-Hyacinthe (Quebec) Canada • J2S 8E3
Phone: 450 771.0777 • 877 711.0777
Fax: 450 771.5779
secco@seccointernational.com
www.linkedin.com/company/secco-international-inc