

MEGAFAN TUNNEL VENTILATION



HIGH PERFORMANCE AND INNOVATIVE DESIGN

- Thick and corrosion-resistant fiberglass housings with lifetime warranty (The 78" (1.98 m) model is grey)
- Totally enclosed, maintenance-free, high efficiency and U-CSA-C or CE-approved motors
- Shipped fully assembled except for discharge cones and guards
- Extremely quiet operation at all speeds
- Automatic belt tensioner on all belt drive fans
- 3-year warranty on the motor and the blades
- Full one-year warranty on all other parts

THE LARGEST EFFICIENT FAN ON THE MARKET ▶
*The 78" (1.98 m) model is grey

SIZE	DRIVE	HP (KW)	VOLT	PH	AMP	RPM	HZ	WATTS USED	CFM (M ³ /H) 0" SP	CFM/WATT (M ³ /H/WATT) 0" SP	CFM (M ³ /H) .05" SP	CFM/WATT (M ³ /H/WATT) .05" SP	CFM (M ³ /H) .10" SP	CFM/WATT (M ³ /H/WATT) .10" SP	CFM (M ³ /H) .15" SP	CFM/WATT (M ³ /H/WATT) .15" SP	CFM (M ³ /H) .20" SP	CFM/WATT (M ³ /H/WATT) .20" SP	SPEED	ROUGH OPENING
36" (91 CM)	BD	1.5 (1.12 kW)	230/460	3	3.4/1.7	700	50/60	1 100	12 000 (20 400 M ³ /H)	11 (18.6 M ³ /H)	11 200 (19 000 M ³ /H)	10.20 (17.3 M ³ /H)	10 100 (17 200 M ³ /H)	9.2 (15.6 M ³ /H)	9 000 (15 300 M ³ /H)	8.2 (13.9 M ³ /H)	7 200 (12 200 M ³ /H)	6.55 (11.1 M ³ /H)	VARIABLE	44" x 44" (112 x 112 CM)
36" (91 CM)	BD	1.5 (1.12 kW)	115/230	1	2.8/5.5	700	50/60	1 100	12 000 (20 400 M ³ /H)	11 (18.6 M ³ /H)	11 200 (19 000 M ³ /H)	10.20 (17.3 M ³ /H)	10 100 (17 200 M ³ /H)	9.2 (15.6 M ³ /H)	9 000 (15 300 M ³ /H)	8.2 (13.9 M ³ /H)	7 200 (12 200 M ³ /H)	6.55 (11.1 M ³ /H)	SINGLE	44" x 44" (112 x 112 CM)
50" (127 CM)	BD	1.5 (1.12 kW)	230/460	3	4.3/2.1	420	50/60	1 100	20 547 (34 909 M ³ /H)	18.7 (31.7 M ³ /H)	19 155 (32 544 M ³ /H)	17.4 (29.6 M ³ /H)	16 375 (27 821 M ³ /H)	14.9 (25.3 M ³ /H)	11 728 (19 926 M ³ /H)	10.6 (18.1 M ³ /H)	9 459 (16 070 M ³ /H)	8.6 (14.6 M ³ /H)	VARIABLE	55" x 55" (140 x 140 CM)
50" (127 CM)	BD	1.5 (1.12 kW)	115/230	1	14.0/7.0	420	50/60	1 100	20 547 (34 909 M ³ /H)	18.7 (31.7 M ³ /H)	19 155 (32 544 M ³ /H)	17.4 (29.6 M ³ /H)	16 375 (27 821 M ³ /H)	14.9 (25.3 M ³ /H)	11 728 (19 926 M ³ /H)	10.6 (18.1 M ³ /H)	9 459 (16 070 M ³ /H)	8.6 (14.6 M ³ /H)	SINGLE	55" x 55" (140 x 140 CM)
72" (183 CM)	BD	3 (2.25 kW)	230/460	3	8.4/4.2	350	50/60	2 000	46 000 (78 200 M ³ /H)	23.0 (39.1 M ³ /H)	44 000 (74 800 M ³ /H)	22.0 (37.4 M ³ /H)	42 000 (71 400 M ³ /H)	21.0 (35.7 M ³ /H)	37 500 (63 750 M ³ /H)	18.8 (31.9 M ³ /H)	35 000 (59 500 M ³ /H)	17.5 (29.8 M ³ /H)	VARIABLE	78" x 78" (198 x 198 CM)
72" (183 CM)	BD	3 (2.25 kW)	230	1	11	350	50/60	2 200	46 000 (78 200 M ³ /H)	20.9 (35.5 M ³ /H)	44 000 (74 800 M ³ /H)	20.0 (34.0 M ³ /H)	42 000 (71 400 M ³ /H)	19.1 (32.5 M ³ /H)	37 500 (63 750 M ³ /H)	17.0 (29.0 M ³ /H)	35 000 (59 500 M ³ /H)	15.9 (27.0 M ³ /H)	SINGLE	78" x 78" (198 x 198 CM)
78" (198 CM)	BD	3 (2.25 kW)	230/460	3	8.4/4.2	355	50/60	2 800	54 960 (93 432 M ³ /H)	19.6 (33.4 M ³ /H)	52 290 (88 893 M ³ /H)	18.7 (31.7 M ³ /H)	51 150 (86 955 M ³ /H)	18.3 (31.1 M ³ /H)	49 120 (83 504 M ³ /H)	17.5 (29.8 M ³ /H)	43 820 (74 494 M ³ /H)	15.7 (26.6 M ³ /H)	VARIABLE	82.5" x 83" H (209 L x 211 H CM)
78" (198 CM)	BD	3 (2.25 kW)	230	1	11.6	355	50/60	2 800	54 960 (93 432 M ³ /H)	19.6 (33.4 M ³ /H)	52 290 (88 893 M ³ /H)	18.7 (31.7 M ³ /H)	51 150 (86 955 M ³ /H)	18.3 (31.1 M ³ /H)	49 120 (83 504 M ³ /H)	17.5 (29.8 M ³ /H)	43 820 (74 494 M ³ /H)	15.7 (26.6 M ³ /H)	SINGLE	82.5" x 83" H (209 L x 211 H CM)

*Secco continues to strive for the most accurate test data available. Information stated above is not certified. As additional independent accredited lab results become available, we may need to revise.

FEATURES

- Balanced heavy-duty corrosion-resistant 6 aluminum blade propeller
- Propeller with 5 black blades reinforced with polyamide fiberglass for the 78" model (1.98 m)
- The 78" fan on high speed produces 54 960 CFM (93 432 m³/h) and 19.6 CFM/watt (33.4 m³/h) at 0" static pressure
- The 78" fan on low speed produces 10 000 CFM (16 990 m³/h) and 30 CFM/watt (50 m³/h) at 0" static pressure
- Optional variable frequency drive allows you a smooth speed adjustment from 355 RPM down to 80 RPM. Fan power consumption is reduced with speed. Make sure you have a minimum shutter opening at a low speed of 1" (2.54 cm)
- All fan performances have been independently tested
- Motor is 3 HP or 2.2 kW on high and 0.3 kW on low 230/460, 3 phase VAC
- All motors are U-CSA-C or CE approved and are 50/60 Hz



For more information
seccointernational.com



Secco International Inc.
4040, Blvd Casavant West
St-Hyacinthe (Quebec) Canada • J2S 8E3
Phone: 450 771.0777 • 877 711.0777
Fax: 450 771.5779
secco@seccointernational.com
www.linkedin.com/company/secco-international-inc

Distributed by: